

WHAT IS CLAIMED IS:

Sub B

1. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;
5 a first top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;
10 a second top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;
15 a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and
a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin
20 film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,
said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.
- 25 2. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;

B1
contd
09453586-120399
SECRET

- a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
- 5 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;
- a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
- 10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;
- a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and
- 15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,
- 20 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.
3. An operation method of an active matrix device comprising:
- a substrate having an insulating surface;
- a first signal line extending over said substrate;
- 25 a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
- a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

B1
Contd

- 5 a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
- 5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;
- a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and
- 10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,
- 15 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.
4. An operation method of an active matrix device comprising:
 - a substrate having an insulating surface;
 - a first signal line extending over said substrate;
 - a first top-gate type thin film transistor having a channel region
 - 20 comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
 - a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;
 - a second top-gate type thin film transistor having a channel region
 - 25 comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
 - a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

09453586 120399

B1
cont'd

a surface smoothing film formed over said first and second thin film transistors;

a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to a source of said second thin film transistor; and

5 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

10 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

5. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

15 a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

20 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

25 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to a source of said second thin film transistor; and

B1
Contd

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

5 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

6. An operation method of an active matrix device comprising:

a substrate having an insulating surface,

10 a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

15 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

20 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

25 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to a source of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

- 5 7. An operation method of an active matrix device comprising:
- a substrate having an insulating surface;
 - a first signal line extending over said substrate;
 - a first top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
 - 10 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;
 - a second top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
 - 15 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;
 - a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and
 - 20 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,
 - 25 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,
 - said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

09463586 120399
66E02T 9855460

B1
contd

045386 120399
66E02T 985E5450

B!
cont'd

8. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;
a first bottom gate type thin film transistor having a channel region
5 comprising crystalline silicon formed over said substrate wherein a gate of said first
thin film transistor is connected to said first signal line;
a second signal line extending across said first signal line wherein
said second signal line is connected to a drain of said first thin film transistor;
a second bottom gate type thin film transistor having a channel region
10 comprising crystalline silicon formed over said substrate wherein a signal is applied
to a gate of said second thin film transistor from said second signal line through at
least said first thin film transistor;
a voltage supply line formed over said substrate wherein said voltage
supply line is connected to a drain of said second thin film transistor;
15 a pixel electrode formed over said substrate wherein said pixel
electrode is connected to a source of said second thin film transistor; and
a driving circuit formed over said substrate for driving at least one of
said first and second thin film transistors, said driving circuit comprising a third thin
film transistor wherein a channel forming region of said third thin film transistor
20 comprises crystalline silicon,
wherein a channel width of said second thin film transistor is larger
than a channel width of said first thin film transistor,
said method comprising a step of applying a voltage from said voltage
supply line to said pixel electrode for a period during one frame, wherein said period
25 is determined in accordance with a desired tone of a display.
9. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;

B!
contd

5 a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

5 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

10 a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

15 a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and

15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

20 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

20 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

25 10. An operation method of an active matrix device comprising:
a substrate having an insulating surface;

a first signal line extending over said substrate;

a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

09453586 120399
65E027 985E460
B1
cont'd

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

5 a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

20 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

11. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

25 a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

5 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

20 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

12. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

25 a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

10 a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

13. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said

B1
contd

substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

10 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

14. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said

B' could

substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

10 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

15. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate

wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

10 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

16. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said

substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

17. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said

B1
cont'd

substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

15 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

18. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate

*B1
cont'd*

wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

19. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

a second top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

B' cont'd

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor; and

a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor;

5 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

10 20. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

15 a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

20 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor; and

25 a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor;

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period

is determined in accordance with a desired tone of a display.

21. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor; and

a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor;

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

22. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said

09453586-120399

B1
centd

substrate wherein a gate of said first thin film transistor is connected to said first signal line;

5 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

10 a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

15 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

20 a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

25 said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

23. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

25 a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

*B1
cont'd*

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

5 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

15 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.

20 24. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate

B1
cont'd

- wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
- a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;
- a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and
- wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,
- said method comprising a step of applying a voltage from said voltage supply line to said pixel electrode for a period during one frame, wherein said period is determined in accordance with a desired tone of a display.
25. An operation method of an active matrix device comprising:
- a substrate having an insulating surface;
- a first signal line extending over said substrate;
- a first top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
- a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;
- a second top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
- a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;
- a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and

09153536-120399
B1
contd

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

5 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

26. An operation method of an active matrix device comprising:

10

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

15

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

20

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and

25

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

- 5 27. An operation method of an active matrix device comprising:
- a substrate having an insulating surface;
- a first signal line extending over said substrate;
- a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;
- 10 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;
- a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
- 15 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;
- a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and
- 20 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,
- 25 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

B' could

28. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;
a first top-gate type thin film transistor having a channel region
5 comprising crystalline silicon formed over said substrate wherein a gate of said first
thin film transistor is connected to said first signal line;
a second signal line extending across said first signal line wherein
said second signal line is connected to a drain of said first thin film transistor;
a second top-gate type thin film transistor having a channel region
10 comprising crystalline silicon formed over said substrate wherein a signal is applied
to a gate of said second thin film transistor from said second signal line through at
least said first thin film transistor;
a voltage supply line formed over said substrate wherein said voltage
supply line is connected to a drain of said second thin film transistor;
15 a surface smoothing film formed over said first and second thin film
transistors;
a pixel electrode formed over said surface smoothing film wherein
said pixel electrode is connected to a source of said second thin film transistor; and
a driving circuit formed over said substrate for driving at least one of
20 said first and second thin film transistors, said driving circuit comprising a third thin
film transistor wherein a channel forming region of said third thin film transistor
comprises crystalline silicon,
said method comprising a step of applying one or more pulses from
said voltage supply line to said pixel electrode during one frame wherein a number
25 of pulses applied to said pixel electrode during one frame is determined in
accordance with a desired tone of a display.
29. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;

a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

5 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

15 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to a source of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

20 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

30. An operation method of an active matrix device comprising:

25 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

B' contd

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

5 a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

10 a surface smoothing film formed over said first and second thin film transistors;

a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to a source of said second thin film transistor; and

15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

20 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

31. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

25 a first top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

*B1
contd*

a second top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and

10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

15 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

32. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied

to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

5 a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

10 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

15 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

33. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

20 a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

25 a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

B1
cont'd

09453586.120399

B!
contd

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor; and

5 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

10 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

15 34. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

20 a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

25 a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

09453586 120399
663027 9855460

B! could

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

5 a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

15 35. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

20 a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

25 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

B1
cont'd

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

5 a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

- 15 36. An operation method of an active matrix device comprising:
- a substrate having an insulating surface;
 - a first signal line extending over said substrate;
 - a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate
 - 20 wherein a gate of said first thin film transistor is connected to said first signal line;
 - a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;
 - a second thin film transistor having a channel region comprising
 - 25 crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

09453586-120390
66E02T-985E5460

B' Cont'd

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

5 a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

15 37. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

20 a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

25 a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

B' could

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

5 a surface smoothing film formed over said first and second thin film transistors;

a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

10 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

38. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;
a first signal line extending over said substrate;
a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said

substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

10 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

39. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

25 a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate

B1
cont'd

wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a surface smoothing film formed over said first and second thin film transistors;

10 a pixel electrode formed over said surface smoothing film wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

40. An operation method of an active matrix device comprising:

20 a substrate having an insulating surface;

a first signal line extending over said substrate;

25 a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

B1
contd

a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

5 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

10 a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

15 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

20 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

41. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;
a first bottom gate type thin film transistor having a channel region
25 comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

B1 cont'd

B1
contd

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

5 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

20 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

25 42. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

5 a second thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

10 a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

15 a driving circuit formed over said substrate for driving at least one of said first and second thin film transistors, said driving circuit comprising a third thin film transistor wherein a channel forming region of said third thin film transistor comprises crystalline silicon,

20 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

25 43. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

5 a second top-gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor; and

10 a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor;

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

15 said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

44. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

20 a first bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

25 a second bottom gate type thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor; and

a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor;

5 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in
10 accordance with a desired tone of a display.

45. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

15 a first thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to a drain of said first thin film transistor;

20 a second thin film transistor having a channel region comprising crystalline silicon formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to a drain of said second thin film transistor; and

25 a pixel electrode formed over said substrate wherein said pixel electrode is connected to a source of said second thin film transistor;

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

- 5 46. An operation method of an active matrix device comprising:
- a substrate having an insulating surface;
- a first signal line extending over said substrate;
- a first top-gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said
- 10 substrate wherein a gate of said first thin film transistor is connected to said first signal line;
- a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;
- 15 a second top-gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;
- a voltage supply line formed over said substrate wherein said voltage
- 20 supply line is connected to one of said second pair of impurity regions of said second thin film transistor;
- a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and
- 25 wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,
- said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number

of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

47. An operation method of an active matrix device comprising:

a substrate having an insulating surface;

a first signal line extending over said substrate;

a first bottom gate type thin film transistor having a channel region comprising crystalline silicon and a first pair of impurity regions formed over said substrate wherein a gate of said first thin film transistor is connected to said first signal line;

a second signal line extending across said first signal line wherein said second signal line is connected to one of said first pair of impurity regions of said first thin film transistor;

a second bottom gate type thin film transistor having a channel region comprising crystalline silicon and a second pair of impurity regions formed over said substrate wherein a signal is applied to a gate of said second thin film transistor from said second signal line through at least said first thin film transistor;

a voltage supply line formed over said substrate wherein said voltage supply line is connected to one of said second pair of impurity regions of said second thin film transistor;

a pixel electrode formed over said substrate wherein said pixel electrode is connected to the other one of said second pair of impurity regions of said second thin film transistor; and

wherein a channel width of said second thin film transistor is larger than a channel width of said first thin film transistor,

said method comprising a step of applying one or more pulses from said voltage supply line to said pixel electrode during one frame wherein a number of pulses applied to said pixel electrode during one frame is determined in accordance with a desired tone of a display.

B1
contd

*B1
contd*

48. An operation method of an active matrix device comprising:
a substrate having an insulating surface;
a first signal line extending over said substrate;
a first thin film transistor having a channel region comprising
5 crystalline silicon and a first pair of impurity regions formed over said substrate
wherein a gate of said first thin film transistor is connected to said first signal line;
a second signal line extending across said first signal line wherein
said second signal line is connected to one of said first pair of impurity regions of
said first thin film transistor;
10 a second thin film transistor having a channel region comprising
crystalline silicon and a second pair of impurity regions formed over said substrate
wherein a signal is applied to a gate of said second thin film transistor from said
second signal line through at least said first thin film transistor;
a voltage supply line formed over said substrate wherein said voltage
15 supply line is connected to one of said second pair of impurity regions of said second
thin film transistor;
a pixel electrode formed over said substrate wherein said pixel
electrode is connected to the other one of said second pair of impurity regions of said
second thin film transistor; and
20 wherein a channel width of said second thin film transistor is larger
than a channel width of said first thin film transistor,
said method comprising a step of applying one or more pulses from
said voltage supply line to said pixel electrode during one frame wherein a number
of pulses applied to said pixel electrode during one frame is determined in
25 accordance with a desired tone of a display.

49. The method according to claim 12 wherein said active matrix device
is a liquid crystal device.

50. The method according to claim 49 wherein each of said first and second thin film transistors is a top-gate transistor.

51. The method according to claim 49 wherein each of said first and second thin film transistors is a bottom-gate transistor.

52. The method according to claim 36 wherein said active matrix device is a liquid crystal device.

53. The method according to claim 52 wherein each of said first and second thin film transistors is a top-gate transistor.

54. The method according to claim 52 wherein each of said first and second thin film transistors is a bottom-gate transistor.

55. The method according to claim 3 wherein said active matrix device is a liquid crystal device.

56. The method according to claim 6 wherein said active matrix device is a liquid crystal device.

57. The method according to claim 9 wherein said active matrix device is a liquid crystal device.

58. The method according to claim 15 wherein said active matrix device is a liquid crystal device.

59. The method according to claim 18 wherein said active matrix device is a liquid crystal device.

SUB
DB

09453586-120399

SUB
DU

60. The method according to claim 27 wherein said active matrix device is a liquid crystal device.

61. The method according to claim 30 wherein said active matrix device is a liquid crystal device.

62. The method according to claim 33 wherein said active matrix device is a liquid crystal device.

63. The method according to claim 36 wherein said active matrix device is a liquid crystal device.

64. The method according to claim 39 wherein said active matrix device is a liquid crystal device.

65. The method according to claim 42 wherein said active matrix device is a liquid crystal device.

66. The method according to claim 45 wherein said active matrix device is a liquid crystal device.

Sub
DU

00453556-120399
66E027-9355460

add B²